

<u> HOOKS</u> TABLE I REFERENCES

- I. ACI Types I thru 262. SHA Standard Pin Bending3. SHA Radius Bending





RECOMMENDED END HOOKS, ALL GRADES						
BAR	Finished bend diameter	180 - deg hook		90 - deg hook		
SIZE	D, in.	A or G in	J, in.	A or G in		
#.3	2 ^l / ₄	5	3	6		
#.4	3	6	4	8		
#5	33/4	7	5	10		
#-6	4 ¹ / ₂	8	6	1-0		
#.7	5 ^l / ₄	10	7	I-2		
#.8	6	Н	8	1-4		
#.9	91/2	1-3	113/4	1-7		
#10	103/4	1-5	- / ₄	1-10		
#	12	1-7	1-23/4	2-0		
#14	18 ¹ / ₄	2-3	1-93/4	2-7		
#18	2:4	3-0	$2-4\frac{1}{2}$	3-5		

APPROVAL			
C.S Freedom DIRECTOR OFFICE OF STRUCTURES			
DATE: /////97			
REVISIONS			

STATE OF MARYLAND
DEPARTMENT OF TRANSPORTATION
STATE HIGHWAY ADMINISTRATION
OFFICE OF STRUCTURES

1127.0.010							
SHA	FHWA	REINFORCING	STFFL	H00K	TABLES	AND	DIAGRAMS
	-						

FHWA APPROVAL		OTANDADD NO DEDAD DD(0.05) 07 320
DATE		STANDARD NO. REBAR-BD(9.05)-97-320

SHEET ____ OF_2